


## Normal-Standard



## T1 Acier Zingué/Zinc plated steel

Réf	Diamètre/size		Dimensions-mm						Poids/weight		CU/WLL	CR/BL
	mm	inch	L.T.	L.I.	A	O	E	T	kg/100pcs	kg	kg	
MRNZ02.5	2,5	3/32"	26,0	21,0	7,0	3,5	8,0	3,5	0,300	35	175	
MRNZ03.0	3,0	7/64"	31,0	25,0	8,5	4,0	9,0	4,0	0,515	50	250	
MRNZ03.5	3,5	1/8"	36,0	29,0	10,0	5,0	11,0	5,0	0,790	100	500	
MRNZ04.0	4,0	5/32"	39,5	31,5	11,5	5,5	12,5	6,0	1,170	180	900	
MRNZ05.0	5,0	3/16"	49,5	39,5	13,0	6,5	16,0	7,0	2,050	280	1 400	
MRNZ06.0	6,0	1/4"	57,0	45,0	14,5	7,5	19,0	9,0	3,450	400	2 000	
MRNZ07.0	7,0	9/32"	66,0	52,0	16,0	8,5	21,5	10,0	5,100	550	2 750	
MRNZ08.0	8,0	5/16"	74,0	58,0	17,5	11,0	24,0	11,0	7,700	700	3 500	
MRNZ09.0	9,0	3/8"	80,0	62,0	19,0	11,0	26,0	12,0	10,250	900	4 500	
MRNZ10.0	10,0	7/16"	89,0	69,0	20,5	12,0	29,0	13,0	13,700	1 100	5 500	
MRNZ12.0	12,0	1/2"	104,5	80,5	23,5	15,0	33,0	15,0	23,200	1 500	7 500	
MRNZ14.0	14,0	9/16"	121,0	93,0	26,5	17,0	38,5	17,0	36,500	2 200	11 000	
MRNZ16.0	16,0	5/8"	140,0	108,0	29,5	19,0	45,0	19,0	56,200	2 900	14 500	
MRNZ18.0	18,0	11/16"	157,0	121,0	32,5	23,0	52,0	22,0	79,320	3 500	17 500	
MRNZ20.0	20,0	25/32"	177,5	137,5	35,5	26,0	60,0	24,0	110,000	4 000	20 000	

## T2 Inox/Stainless steel

Réf	Diamètre/size		Dimensions-mm						Poids/weight		CU/WLL	CR/BL
	mm	inch	L.T.	L.I.	A	O	E	T	kg/100pcs	kg	kg	
MRNI02.5	2,5	3/32"	26,0	21,0	7,0	3,5	8,0	3,5	0,310	100	500	
MRNI03.0	3,0	7/64"	31,0	25,0	8,5	4,0	9,0	4,0	0,530	160	800	
MRNI03.5	3,5	1/8"	36,0	29,0	10,0	5,0	11,0	5,0	0,810	220	1 100	
MRNI04.0	4,0	5/32"	39,5	31,5	11,5	5,5	12,5	6,0	1,200	280	1 400	
MRNI05.0	5,0	3/16"	49,5	39,5	13,0	6,5	16,0	7,0	2,100	450	2 250	
MRNI06.0	6,0	1/4"	57,0	45,0	14,5	7,5	19,0	9,0	3,540	650	3 250	
MRNI07.0	7,0	9/32"	66,0	52,0	16,0	8,5	21,5	10,0	5,230	900	4 500	
MRNI08.0	8,0	5/16"	74,0	58,0	17,5	11,0	24,0	11,0	7,900	1 100	5 500	
MRNI09.0	9,0	3/8"	80,0	62,0	19,0	11,0	26,0	12,0	10,500	1 400	7 000	
MRNI10.0	10,0	7/16"	89,0	69,0	20,5	12,0	29,0	13,0	14,050	1 800	9 000	
MRNI12.0	12,0	1/2"	104,5	80,5	23,5	15,0	33,0	15,0	23,800	2 500	12 500	
MRNI14.0	14,0	9/16"	121,0	93,0	26,5	17,0	38,5	17,0	37,400	3 500	17 500	
MRNI16.0	16,0	5/8"	140,0	108,0	29,5	19,0	45,0	19,0	57,600	4 500	22 500	

## T3 Zicral/Zicral

Réf	Diamètre/size		Dimensions-mm						Poids/weight		CU/WLL	CR/BL
	mm	inch	L.T.	L.I.	A	O	E	T	kg/100pcs	kg	kg	
MRNZIC07.0	7,0	9/32"	66,0	52,0	16,0	8,5	21,5	10,0	1,830	250	1 250	
MRNZIC10.0	10,0	7/16"	89,0	69,0	20,5	12,0	29,0	13,0	4,890	500	2 500	

## T4 Laiton/Brass

Réf	Diamètre/size		Dimensions-mm						Poids/weight		CU/WLL	CR/BL
	mm	inch	L.T.	L.I.	A	O	E	T	kg/100pcs	kg	kg	
MRNL03.0	3,0	7/64"	31,0	25,0	8,5	4,0	9,0	4,0	0,515	45	225	
MRNL03.5	3,5	1/8"	36,0	29,0	10,0	5,0	11,0	5,0	0,790	90	450	
MRNL04.0	4,0	5/32"	39,5	31,5	11,5	5,5	12,5	6,0	1,170	160	800	
MRNL05.0	5,0	3/16"	49,5	39,5	13,0	6,5	16,0	7,0	2,050	250	1 250	
MRNL06.0	6,0	1/4"	57,0	45,0	14,5	7,5	19,0	9,0	3,450	350	1 750	
MRNL07.0	7,0	9/32"	66,0	52,0	16,0	8,5	21,5	10,0	5,100	500	2 500	
MRNL08.0	8,0	5/16"	74,0	58,0	17,5	11,0	24,0	11,0	7,700	650	3 250	

## T5 Nylon

Réf	Diamètre/size		Dimensions-mm						Poids/weight		CU/WLL	CR/BL
	mm	inch	L.T.	L.I.	A	O	E	T	kg/100pcs	kg	kg	
MRNY06.0	6,0	1/4"	59,0	47,0	12,0	8,0	21,0	8,0	0,500	20	90	
MRNY08.0	8,0	5/16"	74,0	58,0	16,0	10,0	25,0	10,0	1,000	25	130	
MRNY10.0	10,0	7/16"	89,0	69,0	20,0	12,0	29,0	12,0	2,000	30	150	

### Couple de serrage (N.m) Tightening torque (N.m)

Ø F	Couple
2,5	0,15
3,0	0,30
3,5	0,60
4,0	0,70
5,0	0,80
6,0	1,20
7,0	2,50
8,0	3,00
9,0	4,50
10,0	7,00
12,0	9,00
14,0	12,00
16,0	18,00
18,0	30,00
20,0	40,00

CU : charge utile / WLL : working load limit  
CR : charge de rupture / BL : breaking load

N.B. - Ne pas utiliser pour du levage / Not for overhead lifting